US009636006B2

(12) **United States Patent**
Kogure

(10) **Patent No.: US 9,636,006 B2**
(45) **Date of Patent: May 2, 2017**

(54) **ENDOSCOPE CLEANING/DISINFECTING APPARATUS**

(71) Applicant: **OLYMPUS CORPORATION**, Tokyo (JP)

(72) Inventor: **Hisato Kogure**, Hachioji (JP)

(73) Assignee: **OLYMPUS CORPORATION**, Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/952,273**

(22) Filed: **Nov. 25, 2015**

(65) **Prior Publication Data**

US 2016/0074912 A1 Mar. 17, 2016

Related U.S. Application Data

(63) Continuation of application No. PCT/JP2014/076308, filed on Oct. 1, 2014.

(30) **Foreign Application Priority Data**

Feb. 19, 2014 (JP) 2014-029891

(51) **Int. Cl.**
A61B 1/12 (2006.01)
A61B 90/70 (2016.01)
(Continued)

(52) **U.S. Cl.**
CPC ***A61B 1/123*** (2013.01); ***A61B 90/70*** (2016.02); ***B08B 3/08*** (2013.01); *A47L 15/4259* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61B 1/123; A61B 90/70; A61B 2090/701
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2009/0065034 A1* 3/2009 Suzuki ..... A61B 1/123 134/56 R
2012/0015671 A1* 1/2012 Lada G06F 1/1616 455/456.1

FOREIGN PATENT DOCUMENTS

CN 101166457 B 4/2010
CN 102473020 A 5/2012
(Continued)

OTHER PUBLICATIONS

Machine Translation of JP2013-106790A, dated Jun. 6, 2013.*
(Continued)

Primary Examiner — Spencer Bell
(74) *Attorney, Agent, or Firm* — Scully, Scott, Murphy & Presser, P.C.

(57) **ABSTRACT**

An endoscope cleaning/disinfecting apparatus includes: a cleaning/disinfecting tank; a cover portion; a facing portion; an approach portion; a central portion; an acceleration sensor detecting an acceleration change pattern at time of the cover portion moving from an open position to a closed position; an informing section; and a control section, when the acceleration change pattern detected by the acceleration sensor is different from a set pattern at the time of the cover portion moving from the open position to the closed position, judging that the approach portion comes into contact with the cleaning/disinfecting target and performing warning control of the informing section. A shortest distance between the approach portion and the cleaning/disinfecting tank at time of the approach portion being fitted into a hollow portion at the closed position is less than 3.2 mm.

8 Claims, 9 Drawing Sheets